

TPWLKW

TPWLKW "LOGISTIC" SERIES PALLET TRUCK SCALE WITH WIDE FORKS



Pallet truck scale, with built-in electronic weighing, fitted with forks 680mm width, which making it ideal for the handling of pallets in the Food & Chemical Industry Sector. Fitted with rechargeable extractable battery. Available also with a built-in printer as well as CE-M DOUBLE RANGE approved.

Working in cooperation with:

**MASSAMATIC PTY LTD**

13 BOOMPIES STREET - 7500 - PAROW-EAST - SOUTH AFRICA  
Tel. 0027-219302510 Fax. 0027-219398488  
sales@massamatic.com

**The best solution  
for advanced industrial  
applications**

## MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy: +/- 0.1% of the maximum capacity in the versions for internal use.
- Accuracy: +/- 0.05% of the maximum capacity in the "M" approved versions.
- Forks dimensions 1240 x 680 x 85 mm.
- Weighs about 134 kg.
- Structure in extra thick steel and oven-fire painted mechanics.
- Steering wheels and double loading poliurethane rollers.
- 4 stainless steel IP68 load cells for the legal for trade use version, aluminium IP67 load cells for the internal use version.
- Weight indicator in IP65 STAINLESS STEEL waterproof case, which is easy to clean and resistant to harsh and corrosive environments; large 25mm LCD display high contrast digits, which are clearly visible even in poor lighting conditions and with low temperatures, and waterproof membrane keyboard, with 17 functional keys.
- Configuration, calibration and diagnostics from keyboard or PC with DINITOOLS.
- Power supply through extractable rechargeable battery mounted on the pallet truck column.
- The operating time is of about 80 hours of continuous use or one month with the tipycal non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function. Battery level indication.
- Equipped with 230Vac 50 Hz battery charger.
- Configurable RS232/C bidirectional port for connection to a printer, with customisable print format.
- Configurable RS232/C bidirectional port for PC, modem radio or portable terminal.
- IR input for remote control management.
- Fitted with thermal printer in the TPWLKWP and TPWLKWPM versions, with Date&Time card.

## MAIN FUNCTIONS

- Zeroing, Tare, Printing
- High Resolution Weighing x 10
- Net/Gross or Ib/kg conversion
- Accumulation
- Formulation
- +/- Checkweighing
- Percentage weighing
- Counting (Max. resolution of 1.500.000 divisions)
- Hold and Peak
- Set Point Control (with optional interface)

## AVAILABLE UPON PRICE ESTIMATE

- Special steering wheels.
- Special fork length from 850 to 1500 mm.
- Special capacity e/o divisions.
- High resolution.

## VERSIONS

## Versioni disponibili

Codice	Max (kg)	d (kg)	<b>M</b> (kg)
TPWLKW	500 / 1000 / 2000	0,2 / 0,5 / 1	--
TPWLKWM <b>M</b>	1000 / 2000	--	0,5 / 1
TPWLKWP	500 / 1000 / 2000	0,2 / 0,5 / 1	--
TPWLKWPM <b>M</b>	1000 / 2000	--	0,5 / 1

NOTA: colonna e timone da montare.



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI AR GEO  
FRANCE sarl  
Nogent-sur-Marne

DINI AR GEO  
GMBH  
Sinsheim - Germany

DINI AR GEO  
UK Ltd  
Taunton - United Kingdom

DINI AR GEO WEIGHING  
INSTRUMENTS Ltd  
Shanghai - China

DINI AR GEO  
WEIGHBRIDGES  
Calto (RO) – Italy



HEAD OFFICE  
Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena - Italy



**MASSAMATIC PTY LTD**

13 BOOMPIES STREET - 7500 - PAROW-EAST - SOUTH AFRICA

Tel. 0027-219302510 Fax. 0027-219398488

sales@massamatic.com

SALES AND TECHNICAL ASSISTANCE SERVICE